

PLC Fiber Optic Splitter



Descriptions

PLC splitter is a high quality passive device. It is especially for passive internet (EPON, BPON, and GPON). The different package can follow clients' different inquiry. Types available include 1XN and 2XN.

Features

- Low insertion loss
- Low excess loss
- Low PDL
- High directivity
- Long haul reliability
- Customer defined specifications

Specifications of 1XN PLC splitters

Parameters		1X2	1X4	1X8	1X16	1X32	1X64
Fiber type		SMF-28e or customer specified					
Operating Wavelength		1260-1650					
Insertion loss(dB)	Max(P/A)	3.8/4.0	7.2/7.4	10.5/10.7	13.5/13.7	16.5/16.9	21
Loss Uniformity(dB)	Max	0.6	0.6	0.8	1.2	1.7	2.5
Return loss(dB)	Min(P/A)	55/50	55/50	55/50	55/50	55/50	50
PDL(dB)	Max	0.2	0.2	0.3	0.3	0.3	0.4
Directivity(dB)	Min	55	55	55	55	55	55
Wavelength Dependent loss(dB)	Max	0.5	0.5	0.5	0.8	0.8	0.8
Temperature Stability(-40~85 °C)(dB)	Max	0.5	0.5	0.5	0.8	0.8	1
Operating Temperature (°C)		-40 to 85					

Specifications of 2XN PLC splitters

Parameters		2X2	2X4	2X8	2X16	2X32	2X64
Fiber type		SMF-28e or customer specified					
Operating Wavelength		1260-1650					
Insertion loss(dB)	Max(P/A)	4	7.8	11.2	14.6	17.5	22
Loss Uniformity(dB)	Max	0.6	0.6	0.8	1.2	1.7	2.5
Return loss(dB)	Min(P/A)	50	50	50	50	50	50
PDL(dB)	Max	0.2	0.2	0.3	0.3	0.3	0.4
Directivity(dB)	Min	55	55	55	55	55	55
Wavelength Dependent loss(dB)	Max	0.6	0.6	0.6	0.8	1	1
Temperature Stability(-40~85 °C)(dB)	Max	0.6	0.6	0.6	0.8	1	1
Operating Temperature (°C)		-40 to 85					