

Front Panel Changeable Fiber Optic Patch Panel**Rack Mounted and Drawer Style
(L×W×H):482×230×45mm****Features****Front panels are changeable.**

The shell is high intensified & insulated material, thus having excellent mechanic performance□

It is solid and durable

Fiber input: 4

Adapters output: 12core

Strength core and shell was insulated and with grounding lead

Suitable for inserting installation of SC, FC, ST and LC adaptor□

Full accessories for convenient operations

Performance

Excellent designCapacity: Maximum 48 cores□

Reliable fiber lead, grounding and perfect fix up

Reliable pigtail fixes up and perfect protection

Apply to extensive field□

Convenient for operations and maintenance

Specifications

Environment temperature: -40°C ~+80°C

Relative humidity: ≤85% (30°C)

Atmosphere pressure: 70~106KPa

Insulated Resistance: ≥2×10MΩ/500V (DC)

Intensity ≤ 15kv (DC) /1min no spark-over and no flying arc

Fiber bending radius guaranteed more than 40mm: ≥40mm

applicable for straight-through connection and diverged connection in aerial layout.

Duct and direct buried.

It can protect fiber connectors commendably.

Part Number HFOPP-RD

For detailed inquiry please contact our sales team at: sales@huihongfiber.com .